

Oxygen Product Data Sheet

Specification

Purity: 99.5%

Grade: 2.5

Impurities*: H₂O <30ppm EINECS: 231-956-9

Cylinders

| Size | Volume | Pressure | Product Code | Height (approx.) | Width (approx.) | Depth (approx.) | Total Weight (approx.) | Valve |
|------|---------|----------|-----------------|------------------|--------------------|------------------------|------------------------------|--------------------|
| 10L | 2.42m³ | 230bar | 522962 | 930mm | 140mm | | 17kg | BS3 |
| 20L | 4.85m³ | 230bar | 523014 | 950mm | 200mm | | 32kg | BS3 |
| 30L | 7.27m³ | 230bar | 523024 | 1190mm | 210mm | | 45kg | EN561 Quick-Action |
| 50L | 12.12m³ | 230bar | 523016 | 1650mm | 210 | mm | 68kg | BS3 |

Packs

| Size | Volume | Pressure | Product Code | Height (approx.) | Width (approx.) | Depth (approx.) | Total Weight (approx.) | Valve |
|----------|----------|----------|-----------------|------------------|--------------------|------------------------|------------------------------|-------|
| 11 x 50L | 133.39m³ | 230bar | 523018 | 1950mm | 1010mm | 670mm | 1100kg | BS3 |
| 16 x 50L | 194.03m³ | 230bar | 523020 | 2050mm | 1050mm | 110mm | 1890kg | BS3 |

^{*} specification relates to raw material certificate of conformity.